

Payanywhere Smart Terminal



Specifications | Sunmi P2



Software	The Payanywhere Application
Operating System	SUNMI OS (Android 11Go)
Processor	Cortex-A53, quad-core 1.5GHz
Memory	1GB RAM+8GB ROM 2GB RAM+16GB ROM (Optional)
Display	5.5" HD+ (720 x 1440) Capacitive multi-touch
Physical Keys	1* Power button 1* Function button
Printer	Built-in 58mm thermal printer Print speed: 70mm per second Paper roll: 40mm
Communications	2G & 3G & 4G Wi-Fi: 2.4GHz/5GHz IEEE 802.11a/b/g/n Bluetooth® wireless technology
Camera	Front: 0.3MP FF (Optional) Rear: 5MP AF + Flashlight 1D/2D barcode scanning
Scanners	2D Barcode scan engine (optional)
Card Readers	Magnetic Card Reader Smart Card Reader Contactless
Battery	Removable LiPo battery 7.6V/2540mAh 3000mah (Optional)
Audio	Speaker: 1* 1W Microphone: 1* MIC
Physical	L x W x H (inches): 8.74 x 3.21 x 0.69 Weight: 14.12 oz (including battery)
Location	Supports GPS AGPS
Peripheral Ports	Card Slot: 2* SIM (Nano&MINI) + 1* PSAM or 1* SIM (Nano) + 2* PSAM MicroSD (TF) up to 128G Port: 1* Type-C, OTG supported
Environmental	Operating Temperature: -10°C - 50°C (14°F - 122°F) Storage Temperature: -20°C - 60°C (-4°F - 140°F)
Voltage	Input: AC 100-240V Output: DC 5V/2A
Accessories	Charging base, supporting USB OTG and Ethernet (optional)
Certifications	PCI PTS 5.x SRED, EMV® L1 & L2, Visa payWave, Mastercard PayPass, American Express expresspay, Discover D-PAS, Interac Flash, JCB J/ Speedy UnionPay qUICS, PTCRB