

Payanywhere Smart Terminal

Specifications | PAX A920 Pro



Software	The PayAnywhere Application
Operating System	PAXBiz® Powered By Android
Processor	32-bit 4core Cortex A53, 1.4GHZ 32-bit RISC Core ARMv7(Dedicated Encryption)
Memory	1GB RAM + 8GB Flash, Micro SD Card Slot Supports up to 128GB
Display	5.5" (720 x 1440) IPS Touchscreen Display
Physical Keys	1 x ON/OFF Key 2 x Shortcuts
Printer	2" Thermal Printer 80mm Per Second
Communications	4G LTE Dual Band Wi-Fi Bluetooth® wireless technology
Camera	5 MP Auto Focus Rear Camera
Scanner	Standard Laser Scanner or OPTIONAL Professional Laser Scanner
Card Readers	Magnetic Card Reader Smart Card Reader Contactless
Battery	3.7V/5150mAh Li-Ion Battery
Audio	Speaker Functionality Microphone & Sound Wave Payment Supported
Physical	L x W x H (inches): 7.02 x 3.07 x 2.13 Weight: 11.3 oz (including battery)
Location	Supports GPS
Peripheral Ports	Dual SIM 1 x Micro USB
Environmental	0°C – 50°C (32°F – 122°F) Operating Temperature 5% – 95% Relative Humidity, Non-Condensing -20°C – 70°C (-4°F – 158°F) Storage Temperature
Voltage	Input: 100 – 240V AC, 50Hz/60Hz Output: 5.0V DC, 2.0A
Accessories	Charging Base Multi-Functional Base Wireless Base
Certifications	PCI PTS 5.x SRED, EMV® L1 & L2, Visa payWave, Mastercard PayPass, American Express expresspay, Discover D-PAS, Interac Flash, JCB J/ Speedy UnionPay qUICS, PTCRB